

## KIWOCLEAN® EL 9100 MC

### Biodegradable, aqueous-alkaline screen-cleaner for reflow solder facilities

KIWOCLEAN EL 9100 MC is a special, efficient cleaning product for the manual cleaning of fluxing agents and fluxing agent condensates after the soldering process. KIWOCLEAN EL 9100 MC has low odour, is biodegradable and free of aromatic and aliphatic hydrocarbons

#### APPLICATION

Spray KIWOCLEAN EL 9100 MC on the surface, let it react for some minutes and rinse thoroughly with water. KIWOCLEAN EL 9100 MC can be used on both cold and warm surfaces.

Notice: KIWOCLEAN EL 9100 MC consists partly of organic solvents, which may attack various plastics, lacquers or coatings. Therefore please check if working tools, accessories, floor or wall coatings are resistant against KIWOCLEAN EL 9100 MC. Carry out tests in advance.

#### PRODUCT DATA

Colour	colourless, clear
Flash point	n.a.
Boiling range	approx. 100-225°C
Steam pressure (20°C)	approx. 31 mbar
Density (20°C)	approx. 0,99g / cm <sup>3</sup>
Surface tension	approx. 30,6 mN/ m
pH value	approx. 11
Hazard class (VbF)	n.a.
Biodegradable	yes

#### HEALTH HAZARDS/ ENVIRONMENTAL PROTECTION

When working with KIWOCLEAN EL 9100 MC it is recommended to wear suitable safety goggles and gloves. Do not breathe fumes and ensure sufficient ventilation of the working areas.

Please follow further information given in the material safety data sheet.

#### STORAGE

2 years (at 20-25°C and original container)